



NOTES

- 1) CAPACITANCE VALUES: 0.22 μ F GMV, "C" CIRCUIT
- 2) LEADS THREAD SERIES: 5/16"-32
- 3) MATERIALS: DIELECTRIC: MLC DISCOIDAL CAPACITOR
 LEAD: COPPER ALLOY, SILVER PLATED
 BUSHING AND NUTS: BRASS, SILVER PLATED
 INSULATORS: DELRIN (70°C) OR TEFLON (125°C)
- 4) WORKING VOLTAGE: 200 VDC, 140 VAC
- 5) CURRENT RATING: 200 AMP, CONTINUOUS
- 6) DIELECTRIC WITHSTANDING VOLTAGE: 707 VDC, 2 SEC.
- 7) INSERTION LOSS:

| | | |
|----------------|-----------------|----------------|
| 1 MHz – 20 dB | 30 MHz – 50 dB | 1 GHz – 50 dB |
| 3 MHz – 30 dB | 100 MHz – 50 dB | 10 GHz – 50 dB |
| 10 MHz – 40 dB | 300 MHz – 50 dB | |
- 8) OTHER CAPACITANCE VALUES AVAILABLE. CONSULT THE FACTORY.

| | | | | | | | | | | | | | | | | | | | | | | | |
|----------|----------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| C.O. REV | A | | | | | | | | | | | | | | | | | | | | | | |
| DATE | 11/28/06 | | | | | | | | | | | | | | | | | | | | | | |

ALL DIMENSIONS ARE IN INCHES (mm)

GENERAL TOLERANCES UNLESS OTHERWISE SPECIFIED

DECIMAL: $\pm .025$ [.64]

ANGLES: $\pm 1^\circ$

CAGE CODE
15717



One Plastics Rd. – Corry, PA 16407
 (814) 664-7728 FAX (814) 664-4582
 www.cormic.com

Dwg By: RPM Date: 11/28/06 Chk'd By: RPM

Scale: 1X File: Sheet:

HI CURRENT FEEDTHRU SERIES DRAWING – 200 A

HFT1-03-224P