



FT40-02-101P/C SPANNER FEEDTHRU



#0-80 UNF-2A THREAD
[X.XX = MILLIMETERS]

Materials:

Case: C12L15 Cold Rolled Steel
Lead: UNS-C-10200 Oxygen Free Copper.
Finish: Gold Plate per Mil-G-45204, Type III, Grade A.
over .000050" Min Nickel per QQ-N-290.
Epoxy Sealed, Both Ends.

Mounting Torque: 10 in-oz Max.

Maximum Soldering Temperature: 260°C

Operating Temperature: -55°C to +125°C.

Insulation Resistance @ 25°C, 200 VDC: 10G Ω Min.

Dissipation Factor: 3% Max (1 KHz, 1 Vrms).

Current Rating: 1 Amp DC Max.

All electrical testing per MIL-Std-202.

All units 100% production tested, and QC sampled per 0.65% AQL Electrical, 1.5% Mechanical prior to shipment.

PART NUMBER	CAPACITANCE 1 KHz 1 Vrms	TOLERANCE	WVDC (Max)	DWV (5 Sec)	TYPICAL NO LOAD INSERTION LOSS (dB) @ 25°C PER MIL-STD-220			
					10 MHz	100 MHz	1 GHz	10 GHz
FT40-02-101P/C	100 pF	-0% +100%	200	500	-	3	20	28

CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

**Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407
(814) 664-7728 Fax (814) 664-4582 www.cormic.com**

Corry Micronics Inc, herein referred to as CMI, believes this information to be accurate, but makes no warranties, expressed or implied, as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential, arising from the use of our products. User assumes all risk whatsoever, in connection with it's intended use. CMI also reserves the right to change this document without notice.