



CORRY MICRONICS, INC PRODUCT SPECIFICATION

CMISP4T-4080P05A

Single Pole Four Throw Absorptive Switch

Electrical Specifications

Parameters	Specification
Switch Type	Absorptive
Frequency Range	4 ~8 GHz
Insertion Loss	≤2.2 dB
VSWR	≤1.5:1
Isolation	≥60 dB
Max Input Power	+27 dBm CW
Switching Speed	≤50 ns
Power Supply	+5 V (50 mA), -5 V (50 mA)
Control Logic	TTL
Operating Temperature	-40° C ~ +70° C
Input / Output Connector	SMA - Female
Surface Finish	Natural Color Conductive Oxidation
Dimensions	See Attached Drawing (Dimensions are in mm)

Truth Table

E1	E2	E3	E4	J1	J2	J3	J4
0	1	1	1	On	Off	Off	Off
1	0	1	1	Off	On	Off	Off
1	1	0	1	Off	Off	On	Off
1	1	1	0	Off	Off	Off	On

CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407


(724) 940-7556 ext. 138 Fax (724) 940-7707 www.cormic.com

Corry Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with its intended use. CMI also reserves the right to change this document without notice. 06/24/2019



CORRY MICRONICS, INC PRODUCT SPECIFICATION

Outline Drawing:



CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407
(724) 940-7556 ext. 138 Fax (724) 940-7707 www.cormic.com

Corry Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with its intended use. CMI also reserves the right to change this document without notice. 06/24/2019